

# ULTRACARE GROUT PROTECTOR

Water dispersion for protecting cementitious grouts and porcelain tiles



## WHERE TO USE

**UltraCare Grout Protector** is a stain-resistant protector specifically formulated for joints sealed with cementitious grouts and for polished porcelain tiles.

## TECHNICAL CHARACTERISTICS

When applied on the grouted surface, **UltraCare Grout Protector** gives a durable and periodically renewable (according to use and exposure) stain-resistant protection, both to the polished porcelain tiles and the cementitious grouts (CG class according to EN 13888).

The product does not alter appearance, colour or shine of the surface and does not create a film over it. It is a quick-drying treatment.

Treated surfaces are also suitable for contact with foodstuffs.

**UltraCare Grout Protector** has excellent UV stability and retains good protective capacities even after multiple washings. We advise to clean using either **UltraCare Multicleaner Spray** or **UltraCare Multicleaner**, always referring to the respective Technical Data Sheets.

It is resistant to traffic, does not form a film on the surface and has very little effect on the breathability or anti-slip properties of the material. The treatment can be carried out with this single product and surfaces are already set to light foot traffic 2 hours after application (in normal conditions of +23°C and 50%R.H.).

Treated surfaces in damp environments are ready for use in 12 hours.

## RECOMMENDATIONS

The product is not suitable for treating surfaces different from those specified (use other products of the **UltraCare** range, referring to the respective Technical Data Sheets). Always carry out a preliminary test on a hidden sample area, to evaluate the aesthetic result before applying the product on the whole surface.

The treatment may be repeated after a certain period of time to maintain its effect, according to the type of material, the traffic load and wear level of the surface.

Do not apply the product on exposed surfaces if rain is forecast within the next few hours after application.

**UltraCare Grout Protector** is applied on completely cured cementitious grouts which already underwent after-laying acid cleaning. Curing times vary according to the type of grout used for filling the joints (always refer to the respective Technical Data Sheet).

If the product is used in interior, make sure the room is well aerated during application and drying.

## APPLICATION PROCEDURE

**UltraCare Grout Protector** is supplied ready to use in bottles, with nebuliser to ease its application. Shake well before application.

Clean the surface in advance using a suitable cleaner from **UltraCare** range (such as **UltraCare Keranet**, **UltraCare HD Cleaner**, **UltraCare Multicleaner**, etc.), always referring to the respective Technical Data Sheets. Apply **UltraCare Grout Protector** evenly, avoiding the build-up of excess product and spreading it using a fleece applicator or a microfibre cloth. Remove any excess product or dulling before it dries by brushing the surface with a sponge or cloth.

Avoid application on very cold or very hot surfaces ( $> +35^{\circ}\text{C}$  o  $< +5^{\circ}\text{C}$ ). It is advisable to wash the surfaces treated with **UltraCare Grout Protector** using neutral detergents (such as **UltraCare Multicleaner**, diluted according to directions given in the respective Technical Data Sheet). Any excess product can be removed even when completely dry by brushing the surface with a microfibre cloth or by applying a solution of **UltraCare Multicleaner** with a soft abrasive pad and subsequent rinse with clean water.

## CONSUMPTION

Up to 30 m<sup>2</sup> of porcelain tiles surface using one 750 ml flask of **UltraCare Grout Protector** (one coat), according to the surface finish of the material. If applied only on grouts, the product covers up to 800 linear metres. This value is heavily influenced by grouts dimensions and absorption rate.

## PACKAGING

**UltraCare Grout Protector** is supplied in 0.75 litre bottles with spray.

## STORAGE

**UltraCare Grout Protector** may be stored for 3 years in its original packaging.

## SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found on the latest version of the Safety Data Sheet, available from our website [www.mapei.com](http://www.mapei.com).

PRODUCT FOR PROFESSIONAL USE.

## TECHNICAL DATA (typical values)

### PRODUCT IDENTITY

<b>Consistency:</b>	homogeneous liquid
<b>Colour:</b>	colourless
<b>pH (+20°C) neat product:</b>	6.5
<b>Density:</b>	+20°C : 1.00 g/cm <sup>3</sup>
<b>EMICODE:</b>	EC1 Plus – very low emissions

### APPLICATION DATA

<b>Dilution ratio:</b>	ready to use
<b>Surface drying:</b>	4-8 hours

Application temperature range:

+5°C to +35°C

## WARNING

*Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.*

**Please refer to the current version of the Technical Data Sheet, available from our website [www.mapei.com](http://www.mapei.com)**

## LEGAL NOTICE

*The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.*

*The most up-to-date TDS can be downloaded from our website [www.mapei.com](http://www.mapei.com).*

**ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.**

11013-5-2022-1-gb

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

